Industrial and Commercial

G84-4400 Ultraslim Series Keyboards

Durable Ultraslim Keyboards with Mechanical Keyswitch Technology for Industrial and Commercial Aplications

Main Applications

- Rack Mount Systems
- Airlines
- Banking
- Education/Schools
- Manufacturing
- Medical Equipment
- Automotive Equipment
- Office/Data Entry
- White Box PCs
- Field Services
- Test Equipment
- Kiosk Applications
- POS/POT
- Transport

Key Features

- Mechanical Keyswitches are Rated at 20 Million Actuations to Withstand Harsh Environments and Ensure Long Product Lifetime
- Size-reduced QWERTY Key Layout in Ultraslim 15" Form Factor Combines Maximal Space Efficiency with Comfortable Alphanumeric Data Entry
- “FN-Key” for Easy Access of Integrated Numeric Area Ensures Complete Function Support as with Full Size Keyboards
- All Available with PS/2 and USB Interface.
- Ultraflat Trackball for Easy Cursor Navigation at Minimized Space
- “Non-Windows” key layout

Main Part Numbers

G84-4400PPBUS-0
Light grey 15" ultraslim PS/2 keyboard with trackball. US space reduced 83 position key layout without 'Windows keys', 2 PS/2 connectors. Mechanical keyswitches with tampoprinted keycaps.

G84-4400PRBUS
Black 15" ultraslim PS/2 keyboard with trackball. US space reduced 83 position key layout without 'Windows keys', 2 PS/2 connectors. Mechanical keyswitches with tampoprinted keycaps.

G84-4400PTBUS
Black 15" ultraslim USB keyboard with trackpad. US space reduced 86 position key layout. Includes USB and PS/2 connectors. Mechanical keyswitches with tampoprinted keycaps.

Additional product versions on request.

Industrial and Commercial Applications

Ultraslim G84-4400 Series Keyboards

Part Number Legend

G84-4400

G84-4400

Technical Data

Interface
PS/2, USB

Current Input
max. 100 mA

Trackball
Diameter: 16mm
Two switch-activated mouse buttons

Cable Length
Approx. 1.75 m

Key Layout
Sized reduced 83 key layout

Weight (without/with packaging)
0.6/0.7 kg

Dimension
370 x 139 x 20 mm (keyboard)
372 x 141 x 22 mm (packaging)

Packaging Units
124 per master carton
2 master cartons per pallet

Keyswitch Lifetime
20 million operations

Storage Temperature
-20°C to 60°C

Operating Temperature
0°C to 50°C

Approvals
cURus, FCC, CE, VDE, C-Tick, VCCI, GOST-R (PS/2 version also: RRL, BSMI)

Delivery Volume
Keyboard, Quick Guide,

Warranty
2 years

For information on repairs or warranty status contact:
Cherry Technical Support
Phone: 800.510.1689
E-Mail: keyboardsupport@cherrycorp.com

Contact

Call, fax or visit our website for more information.

Last Update: 1/01/07

Cherry Electrical Products
11200 88th Avenue
Pleasant Prairie, WI 53158
Phone: 262.942.6500
Web: www.cherrycorp.com
E-Mail: sales@cherrycorp.com
Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2007 Cherry Electrical Products